Fujitsu recommends Windows 11 Pro.



Data Sheet Fujitsu Tablet STYLISTIC Q5010

Tough Tablet for Hard Work

The FUJITSU Tablet STYLISTIC Q5010 enables new levels of productivity in industrial settings. It is made for rough environments thanks to its spill and dust proof housing (IP54). The lightweight design combined with a 10.1-inch display with reinforced corners. Ultimate connectivity and security options like LTE and fingerprint sensor as well as a long battery runtime let you stay connected wherever you are.

Made for rough and tough environments

Discover new levels of productivity in rough industrial settings

- Spill and dust resistant design with port caps to protect the interfaces (IP54)
- Solid housing with reinforced corners ensures durability
- Durability is MIL-STD-810H tested
- Optional TPU cover for more robustness

Convenience and mobility

All day productivity for indoor and outdoor use

- 10.1" anti-glare touch screen with pen support
- Integrated pen garage
- High performance battery with increased charging voltage (up to 80% in one hour)

Enterprise connectivity and security Secure data access from everywhere

- Embedded 4G/LTE
- Optional keyboard dock with additional LAN port
- Integrated fingerprint sensor
- Family concept: Uses the same cradle as STYLISTIC Q7 Series













Components

Base unit	STYLISTIC Q5010	STYLISTIC Q5010 LTE
Operating systems		
Operating system pre-installed	Windows 10 Home	
Operating system compatible	FREE Upgrade to Windows 11* *Upgrade timing may vary by c specific hardware (see aka.ms/v	evice. Features and app availability may vary by region. Certain features require vindows11-spec).
Operating system notes	Window 10 releases for a period	end of the product life FUJITSU will continue to test and support all upcoming d of maximum 5 years – depending on the available extension of hardware services ups. For details please see "FUJITSU Service Statement for Windows 10 Semi-Annual-port.ts.fujitsu.com.
Processor	Intel® Pentium® Silver N5030 (4	Cores / 4 Threads, 1.1 GHz)
Hard disk drive		
Hard disk	eMMC SSD	
Hard disk notes	3 , .	n bytes, when referring to hard disk drive capacity. Iso depending on used software. Jerved for system recovery
Display	25.7 cm (10.1-inch), LED backlig	ht, WUXGA, 1,920 x 1,200 pixel, Anti-glare display, 500 cd/m², 1000:1
Multimedia		
Camera	Front camera 2.0 megapixel, re	ar camera 8.0 megapixel with autofocus and light

Base unit

Base unit	STYLISTIC Q5010	STYLISTIC Q5010 LTE
General system information		
Chipset	Integrated in CPU	
Supported capacity RAM	8 GB	
Supported capacity RAM (max.)	8 GB	
Memory slots	LPDDR4 (2400 MHz)	
LAN notes	Virtual MAC address. LAN connector via optional keyboard dock, cradle or optional USB adapter cable	
Integrated WLAN	Intel Dual Band Wireless-AC9560NV with integrated BT 5.0	
BIOS version	UEFI Specification 2.6	
BIOS features	InsydeH2O BIOS	
Audio type	On board	
Audio codec	Realtek ALC255	
Audio features	2x internal microphones, 2x built-in	speakers (stereo)
Waterproof / Spillproof	IP54	
Drop resistant	yes	
Dustproof	Yes	
Disinfectable	no	
MIL-STD tested	Yes, selected MIL-STD-810H tests passed.	
	MIL-STD-810H test results are not a guarantee of future performance under identified test conditions.	
	Accidental damage is not covered under standard international limited warranty.	
Display		
Diagonal Size	25.7 cm (10.1-inch)	25.7 cm (10.1-inch)
Display Technology	IPS	IPS

Display		
Display Display type	Anti-glare touchscreen	Anti-glare touchscreen
Display Resolution type	WUXGA	WUXGA
Resolution (native)		
	1,920 x 1,200 pixel	1,920 x 1,200 pixel
Aspect ratio	16:9	16:9
Brightness - typical	500 cd/m ²	500 cd/m ²
Contrast - typical	1000:1	1000:1
Viewing angle (h/v) - typical	160°/160°	160°/160°
Display notes	Wide-view high-bright LED display (for enhanced outdoor viewing) Integrated ambient light sensor for automatic backlight adjustment to the working environment. Toughened glass	
Sensors	Ambient Light Sensor	Ambient Light Sensor
	Compass	Compass
	Gyroscope	Gyroscope
	Proximity	Proximity
Digitizer / Touch Technology	Multi-touch up to 10 fingers, active pen support	Multi-touch up to 10 fingers, active pen support
Pen	EMR 4k pressure level Pen garage inductive charging	
Ambient light sensor	Integrated	Integrated
Ambient light sensor notes	While enabled, the ambient light sensor automatically adj	usts the display backlight
Graphics		. , ,
Base unit	STYLISTIC Q5010	STYLISTIC Q5010 LTE
Graphics brand name	Intel® UHD Graphics 605	Intel® UHD Graphics 605
Graphics features	Dual Display support (1x external, 1x internal)	Dual Display support (1x external, 1x internal)
Grapines reactives		DirectX® 12
	DirectX® 12 OpenGL® 4.4	
Graphics notes	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator	OpenGL® 4.4
Graphics notes Interfaces	OpenGL® 4.4 Shared memory depending on main memory size and open	OpenGL® 4.4
Interfaces	OpenGL® 4.4 Shared memory depending on main memory size and open	OpenGL® 4.4
Interfaces DC-in	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator	OpenGL® 4.4 erating system 1
Interfaces DC-in Audio: line-out / headphone	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in)	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in)
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out)	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out)
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C HDMI	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C HDMI Ethernet (RJ-45)	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable)	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable)
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C HDMI	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C HDMI Ethernet (RJ-45)	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C HDMI Ethernet (RJ-45)	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C HDMI Ethernet (RJ-45)	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C HDMI Ethernet (RJ-45)	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB)	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB)
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C HDMI Ethernet (RJ-45) Memory card slots	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I 1 (MicroSIM - only for models with integrated 4G/LTE) LAN and VGA available via conversion cable., Ethernet via
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C HDMI Ethernet (RJ-45) Memory card slots SIM card slot Interface Module notes	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I 1 (MicroSIM - only for models with integrated 4G/LTE)
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C HDMI Ethernet (RJ-45) Memory card slots	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I 1 (MicroSIM - only for models with integrated 4G/LTE) LAN and VGA available via conversion cable., Ethernet via
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C HDMI Ethernet (RJ-45) Memory card slots SIM card slot Interface Module notes	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I LAN and VGA available via conversion cable., Ethernet via conversion cable (USB to RJ-45)	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I 1 (MicroSIM - only for models with integrated 4G/LTE) LAN and VGA available via conversion cable., Ethernet via conversion cable (USB to RJ-45)
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C HDMI Ethernet (RJ-45) Memory card slots SIM card slot Interface Module notes Docking connector for Port Replicator	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I LAN and VGA available via conversion cable., Ethernet via conversion cable (USB to RJ-45)	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I 1 (MicroSIM - only for models with integrated 4G/LTE) LAN and VGA available via conversion cable., Ethernet via conversion cable (USB to RJ-45)
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C HDMI Ethernet (RJ-45) Memory card slots SIM card slot Interface Module notes Docking connector for Port Replicator	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I LAN and VGA available via conversion cable., Ethernet via conversion cable (USB to RJ-45) 1	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I 1 (MicroSIM - only for models with integrated 4G/LTE) LAN and VGA available via conversion cable., Ethernet via conversion cable (USB to RJ-45)
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C HDMI Ethernet (RJ-45) Memory card slots SIM card slot Interface Module notes Docking connector for Port Replicator Cradle (Charging or Functional)	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I LAN and VGA available via conversion cable., Ethernet via conversion cable (USB to RJ-45) 1 Cradle	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I 1 (MicroSIM - only for models with integrated 4G/LTE) LAN and VGA available via conversion cable., Ethernet via conversion cable (USB to RJ-45)
Interfaces DC-in Audio: line-out / headphone Audio: line-in / microphone Internal microphones USB 3.1 Gen1 (USB 3.0) total USB 3.2 Gen1 (5 Gbps) total USB Type-C HDMI Ethernet (RJ-45) Memory card slots SIM card slot Interface Module notes Docking connector for Port Replicator Cradle (Charging or Functional)	OpenGL® 4.4 Shared memory depending on main memory size and open 3D accelerator 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I LAN and VGA available via conversion cable., Ethernet via conversion cable (USB to RJ-45) 1 Cradle 1 (19V)	OpenGL® 4.4 erating system 1 1 (combo port with Audio line-in) 1 (combo port with Audio line-out) 2x digital array microphones 1 USB Type-A 1 USB Type-C 1 with power delivery 1 (on optional cradle or via optional adapter cable) - 1 SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC card: 512GB microSDXC card: 200GB (or 128GB) Speed Class: up to UHS-I 1 (MicroSIM - only for models with integrated 4G/LTE) LAN and VGA available via conversion cable., Ethernet via conversion cable (USB to RJ-45)

Cradle (Charging or Functional)		
DisplayPort	1	
VGA	1	
Kensington Lock support	1	
Ethernet (RJ-45)	1 (10/100/1000)	
Wireless technologies		
Antennas	2x dual band for WLAN, Bluetooth shared with WLAN	2x dual band for WLAN, 2x for LTE, Bluetooth shared with WLAN
Integrated WLAN	Intel Dual Band Wireless-AC9560NV with integrated BT 5	5.0
WLAN encryption	WEP, WPA, WPA2	
WLAN notes	Import and usage according to country-specific regulations.	
LTE/UMTS/GPS notes	Including GPS functionality Import and usage according to country-specific regulations.	
Integrated WWAN		LTE Sierra Wireless EM7455 (Cat. 6)
WWAN notes		Including GPS functionality Import and usage according to country-specific regulations. LTE Connection Manager (if configured with 4G/LTE)
GPS		Embedded in 4G module if configured with WWAN
Power supply		
AC adapter	12V / 36W (3A)	12V / 36W (3A)
Notes	35W AC Adapter for usage with system/ min. 90W AC Adapter for usage with Cradle	35W AC Adapter for usage with system/ min. 90W AC Adapter for usage with Cradle
Rated voltage range	100 V - 240 V (AC Input)	100 V - 240 V (AC Input)
Rated frequency range	2.4 GHz- 2.48 GHz	2.4 GHz- 2.48 GHz
1st battery	Li-lon battery 2-cell, 31 Wh, 31 Wh	Li-lon battery 2-cell, 31 Wh, 31 Wh
Battery features	Quick Charge: 80% in 1h	Quick Charge: 80% in 1h
Runtime 1st battery	10 h	10 h
Battery charging time	2.3h	2.3h
Battery notes	Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2018. Refer to www.bapc com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime.	
Dimensions / Weight / Environmental		
Dimensions (W x D x H)	262,8 x 168.9 x 12.4 mm	262,8 x 168.7 x 12.4 mm
	10.3 x 0.65 x 0.48 inch	
Weight	from 605 g slate only	from 620 g slate only
Weight (lbs)	from 1.36 lbs	from 1.39 lbs
Weight notes	Weight may vary depending on actual configuration	
Operating ambient temperature	5 - 35 °C (41 - 95 °F); Packed -10 - 60 °C (14 - 140 °F)	
Operating relative humidity	Running: 20 - 80% (relative humidity); Packed: 20 - 80% (relative humidity)	
Compliance		
Product	STYLISTIC Q5010	
Germany	GS	
Europe	CE CB	
USA/Canada	FCC (depending on configuration)	
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) TCO Certified 8.0 in progress MIL-STD-810H tested	

Compliance	
Russia	EAC
China	ССС
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
Security software	
Additional software (preinstalled)	Adobe® Reader® (pdf reader) CyberLink YouCam (webcam software) Fujitsu Display Manager Fujitsu DeskUpdate (driver and utility tool) ShockSensor Utility Power Saving Utility Fujitsu Plugfree Network (network management utility) EasyGuide online user documentation Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink YouCam (webcam software)
Additional software (notes)	Use of accompanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration.
Manageability	
Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN)
Manageability software	DeskView Client DeskView Instant BIOS Management
DeskView components	Inventory Management BIOS Management Driver Management Security Management Alarm Management
Supported standards	WMI (Windows Management Instrumentation) PXE (Preboot Execution Environment) DMI (Desktop Management Interface) SMBIOS (System Management BIOS) CIM (Common Information Model) WBEM (Web Based Enterprise Management) BootP (made4you)
Manageability link	https://www.fujitsu.com/global/products/computing/pc/manageability/
Security	· · · · · · · · · · · · · · · · · · ·
System and BIOS Security	Absolute Persistence® technology capable BIOS EraseDisk Intel® PTT
User Security	Embedded fingerprint sensor (optional) Hard disk password User and supervisor BIOS password
Warranty	
Warranty period	2 years (for countries within EMEIA)
Warranty type	Bring-in Service / Collect & Return Service (depending on country)
Warranty Terms & Conditions	http://www.fujitsu.com/warranty
Digital bug fixes	Subject to availability and following their generic release for the product, bug fixes and function-preserving patches for product-related software (firmware) can be downloaded from the technical support at: https://support.ts.fujitsu.com/ free of charge by entering the respective product serial number. For application software supplied together with the product, please directly refer to the support websites of the respective software manufacturer.

Warranty		
Product Support - the perfect ex	tension	
Recommended Service	9x5, Onsite Response Time: Next Business Day	
Spare Parts availability	at least 3 years after shipment, for details see https://support.ts.fujitsu.com/	
Service Weblink	http://www.fujitsu.com/emeia/products/product-support-services/	

Recommended Accessories

STYLISTIC Q7311, Q7310 and STYLISTIC Q5010 Family Cradle



Flexibility, expandability, desktop replacement, investment protection – to Order Code: name just a few benefits of Fujitsu's docking options.

S26391-F3397-L100

LAN Conversion Cable (USB to LAN) for STYLISTIC Q



The FUJITSU USB Type-A to LAN Conversion Cable enables you to connect Order Code: your compatible STYLISTIC Tablet to a wired network connection.

S26391-F3398-L840

GBit-LAN via USB conversion cable is limited to 480 Mbit/s due to USB 2.0 specification. (Picture similar to product)

USB-C Hub 4 Ports



Fujitsu offers the first most powerful USB-C hybrid usage hub, following industrial requirements as well as being ready for office desktop usage. The USB-C Hub 4 Ports from Fujitsu makes connecting all of your USB peripherals a quick and simple process. SuperSpeed USB Type-C makes data transfer to and from external storage faster than ever. The hub dynamically selects the optimal speed for each device, giving you more bandwidth where you need it automatically.

Order Code: S26391-F6099-L404

Order Code:


FPCSK769BP

Tablet Stand for STYLISTIC O devices



The tablet stand is designed for STYLISTIC devices like latest STYLISTIC Q7312 and can be used universally. Fits for STYLISTIC Q5 and Q7 and the Type-C as well as the Thunderbolt [™] 4 port replicator can be fixed on the

STYLISTIC Q5010 Stylus Pen



Order Code: S26391-F3309-L510

Folio Cover STYLISTIC O5010



The Folio Cover for the STYLISTIC Q5010 is a thin, tailored protective sleeve Order Code: for your Fujitsu tablet. It keeps the device safe from damage on the go, and S26391-F3609-L100 brings a touch of style to your daily work. It can even be used as a stand if you need to display a presentation or watch a clip and fits even the device is connected to its keyboard dock.

STYLISTIC O5010 TPU Cover



The protective TPU Cover is designed to prevent damages to your STYLISTIC Q5010. Openings of the cover allow you to access all ports and buttons whilest the hand strap on the back of the case fives you a firm grip while working with your tablet outside the office.

Order Code: S26391-F3609-L200

Car Adapter USB-C-QC



One Car Adapter fits all. Independent of your mobile device charging method this car adapter will fulfill all major requirements and standards for fast charging vendorbrandindependent notebooks and all mobile devices. The Car Adapter USB-C-QC supports USB PD with PPS, Quick Charge (QC), Apple- and Samsung

Order Code: S26391-F2613-L630

Order Code: S26391-F1194-L125

Notebook Mouse M420NB



The Notebook Mouse M420NB is the perfect optical notebook mouse for busy professionals on the road. It is compact enough that it easily slips into S26381-K454-L100 a notebook bag or briefcase without getting in the way. It features two buttons and a scroll wheel which can also be used as a third button.

Order Code:

STYLISTIC Q5010 Keyboard Dock



Enjoy the benefits of a physical keyboard dock connection which is more reliable and hassle free. With the attached keyboard dock you get the ability to prop the tablet up and fold it over the tablet's screen to protect it, especially when you are mobile.

Order Code: S26391-F3409-L221

More information

Fujitsu products, solutions & services

In addition to Fujitsu Tablet STYLISTIC Q5010, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products www.fujitsu.com/global/products/computing/

Software www.fujitsu.com/software/

More information

Learn more about Fujitsu Tablet STYLISTIC Q5010, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/emeia/products/computing/pc/tablets

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT

Please find further information at http://www.fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.

Copyright 2022 Fujitsu Technology Solutions GmbH

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

The overall product has been designed and manufactured for general office use, regular personal use and ordinary industrial use.

Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com 2023-01-02 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html
Copyright 2022 Fujitsu Technology Solutions GmbH