

Data Sheet

Fujitsu Storage ETERNUS AF650 S3 All-Flash Array

Storage Unchained



ETERNUS AF Storage

FUJITSU Storage ETERNUS AF series are incredibly fast and flexible all-flash storage systems for the next-generation data center. At an affordable price point, it makes flash the new normal for all tier-1 applications in enterprise IT. Response times are ultra-low – in fact, they set performance records. The ETERNUS AF is also built to be smart, with easily configurable automated quality of service to ensure each app gets the performance it needs, plus flexible deduplication and compression (except ETERNUS AF150) that can be turned on when required – and off when not. It keeps data safe with full-fledged DR with mirroring and automated transparent failover.

ETERNUS AF650 S3

The Fujitsu Storage ETERNUS AF650 S3 delivers leading storage performance and automated quality of service management, enabling a maximum of system utilization and contributing to a fast ROI. It is the perfect solution when consolidating data of large-scale databases, business-critical applications and business analytics / big data – all into one all-flash system. Extensive high-availability and disaster recovery capabilities make ETERNUS AF650 an ideal storage system for any business data.



Features & Benefits

Main Features	Benefits
Flexible and flash optimized storage	<ul style="list-style-type: none">■ Ultra-low response times for all applications and a massive increase of IOPS without complicated tuning measures as well as scalable capacity and connectivity.
Selective use of deduplication / compression	<ul style="list-style-type: none">■ Data reduction at the volume level to improve storage efficiency and increase the lifespan of flash
Automated Quality-of-Service	<ul style="list-style-type: none">■ Control applications priorities according to business needs, minimize admin efforts, automate monitoring and adjustment to guarantee service levels
Transparent failover and Storage Cluster	<ul style="list-style-type: none">■ High redundancies enable business critical computing, data processing and real time data mirroring at the highest level and a system availability of up to 99.9999%.
Based on ETERNUS DX high-performance family architecture	<ul style="list-style-type: none">■ Performance-optimized design with proven and mature technology allows system availability of 99.9999%, along with seamless management across ETERNUS AF and ETERNUS DX storage systems.
Convincing access performance and latency	<ul style="list-style-type: none">■ Sufficient performance for all applications requiring high data rates and low response times
<ul style="list-style-type: none">■ Random access performance: Up to 920,000 IOPS (8 KB Blocks)■ Sequential access performance: Max. 22 GB/s (128 KB Blocks)■ Latency: Less than 1 ms (4 KB Blocks)	

Technical details

General system information

ETERNUS AF650 S3	
No. of controllers	2
No. of host interfaces	4-32 ports [FC(32Gbit/s,16Gbit/s)], 4-16 ports [iSCSI(10Gbit/s,1Gbit/s)]
Maximum System Memory	1,536 GB
Maximum Disk Drives	1,056
Max. no. of drive enclosures	43
Supported RAID levels	0, 1, 1+0, 5, 5+0, 6
Host Interfaces	Fibre Channel (16 Gbit/s, 32Gbit/s) iSCSI (10 Gbit/s [10GBase-SR, 10GBase-CR], 1 Gbit/s)
Mixed host interfaces	Yes
Max. no. of hosts	4,096
Maximum Storage Capacity	32,440 TB
Drive Type	2.5-inch, SSD (30.72TB / 15.36TB / 7.68TB / 3.84TB / 1.92TB / 960GB) 2.5-inch, SSD (FIPS) (7.68TB / 3.84TB / 1.92TB)
Drive interface	Serial Attached SCSI (12 Gbit/s)
Back-end disk connectivity	4 pairs of four-lane x 12 Gbit/s Serial Attached SCSI buses (SAS 3.0 wide)
Max. no. of RAID groups per system	528
Max. no. of LUNs per RAID group	128
Max. no. of LUNs	16,384
Max. LUN capacity	128 TB
No. of snapshots - max.	8,192
Max. no. of copy generations	512
Deduplication	Yes
Compression	Yes
Compatibility note	If and to the extent a list of components or certain compatibilities are specified in the product data sheet, these component lists and compatibility specifications are exhaustive. Using deviating or other system components and applications together with the product may but does not necessarily have to lead to compatibility problems. A final statement and/or commitment on the compatibility of such deviating or other system components and applications can only be provided after a corresponding verification through a dedicated compatibility testing.

Performance

Latency	140µsec (Read), 60µsec (Write)
Sequential access performance	22,000 MB/s (128KB Read) 11,000 MB/s (128KB Write)
Random access performance	920,000 IOPS (8KB Read) 670,000 IOPS (8KB Write)
Note	To the extent that specific performance specifications for the product are indicated in the product data sheet, these are usually also dependent on the specific use and workload of the product and may therefore not be reached equally in all application situations. Such performance specifications thus do not represent a specifically agreed characteristic or feature of the product, but only serves as an orientation. The responsibility for a sufficient sizing of the overall system functionality lies solely with the user.

Performance management

Automated Storage Tiering	Yes
Quality of Service	Yes
Operation Management Client	Microsoft Internet Explorer 10, 11, Firefox ESR 60, ESR 68, Microsoft Edge 25, 42, 44, Google Chrome 60, 75, Chrome® 47, 50 (Android®), Safari 8, 9 (iOS)
Note	Automation options can be activated via ETERNUS SF Software. Use of browser software is subject to proactive acceptance of the respective License Agreements/ EULAs of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional.

Continuity management

Storage Cluster	Yes
-----------------	-----

Continuity management

Remote Copy functionality	Synchronous and asynchronous
Note	The product may in connection with and depending on the specific configuration include elements to support time- and performance-critical applications, however high availability (e.g., 99.9999%) and failsafe performance is not a standalone product feature. If and to the extent the product is to be used in such business-critical environments, it is within the sole responsibility of the user to set up the specific additional technical features (e.g., Storage Cluster), redundancies, and operational conditions as required to ensure such high availability or failsafe performance.

Information security management

Data confidentiality	HTTPS (SSL), SSH, CHAP, Bidirectional CHAP
Data integrity	Data Block Guard, Data Encryption, Cache Protection, Disk Drive Patrol, Global Hot Spare, Dedicated Hot Spare, Copy back less, Drive shield, Fast Recovery
Note	The properties of the product provide a baseline for product security and therefore end-customer IT security. However, these properties are not sufficient on their own to protect the product from all existing threats, such as intrusion attempts, data exfiltration and other forms of cyberattacks. To customize security settings, please use the configuration options as available for the respective product. During operation, the IT security of this product is within the responsibility of the respective administrator/end-user of the product. Please note, that Fujitsu as a manufacturer does not make any policy prescriptions or advocacy statements regarding IT security best practices and/or general product operation.

Availability management

Non-disruptive firmware upgrade	Yes
Hot part replacement	Yes

Capacity management

Thin Provisioning	Yes
RAID migration	Yes
Hot part expansion	Yes
Non-disruptive firmware upgrade	Yes

Management

Interfaces	Ethernet (1000 Base-T / 100 Base-TX / 10 Base-T)
Supported protocols	SNMP (version1, 2C, 3), SMI-S 1.4
Administration	Web-based graphical user interface, CLI (Command Line Interface), ETERNUS SF

Supported OS for ETERNUS SF

Operation Management Server	Microsoft® Windows Server® 2019 Microsoft® Windows Server® 2016 Microsoft Windows Server 2012, 2012 R2 Solaris® 11 (11/11 or later) Solaris® 10 (except ETERNUS SF Express) Red Hat Enterprise Linux 8 Red Hat® Enterprise Linux® 7 Red Hat® Enterprise Linux® 6 Oracle Linux 6 VMware® vSphere® 6.0, 6.5, 6.7 Microsoft Windows Server 2019 Hyper-V Microsoft Windows Server 2016 Hyper-V Microsoft Windows Server 2012 Hyper-V, 2012 R2 Hyper-V
Operation Management Client	Microsoft Internet Explorer 10, 11 Firefox ESR 60, ESR 68 Microsoft Edge 25, 42, 44 Google Chrome 60, 75 Chrome® 47, 50 (Android®) Safari 8, 9 (iOS)
Note	See the ETERNUS SF datasheet for further options. Use of certified or supported operating systems and virtualization software is subject to proactive acceptance of the respective License Agreements/ EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration.

Installation specification

19" rackmount	Yes
---------------	-----

Installation specification

Power voltage	AC 200 - 240 V	
Power frequency	50 / 60 Hz	
Power supply efficiency	92 % (80 PLUS gold)	
Maximum Power Consumption	AC 200 - 240 V: 19,830W (20,280VA)	
Power phase	Single	
Dimensions (W x D x H)	ETERNUS AF650 S3	2.5-inch Drive Enclosure
	482 x 805 x 133 mm	482 x 540 x 88 mm
	19 x 31.7 x 5.2 inch	19 x 21.3 x 3.5 inch
Weight	3 U	2 U
	54 kg (119 lb)	35 kg (77 lb)

Environment

Maximum Heat Generation	AC 200 - 240 V: 73,630: kJ/h
Operating environment	FTS 04230 – Guideline for Data Center (installation specification)
Operating environment link	http://docs.ts.fujitsu.com/dl.aspx?id=589915e9-1bf8-40f7-8ba4-7cac9371f2f0

Compliance

Product	ETERNUS AF650 S3
Model	MG-CE
Product safety	UL 60950-1, CSA 60950-1, EN 60950-1, IEC 60950-1, TP TC 004/2011, CNS14336
Electromagnetic Compatibility	FCC Part-15 Subpart B Class A, ICES-003 Class A, EN 55022 (2010), +AI, VCCI Class A, AS/NZS CISPR 22 Class A, CNS13438 (C6357) Class A, KN22
Electromagnetic Immunity	EN 55024
Environmental compliance	RoHS compliant, WEEE compliant
Compliance notes	There is general compliance with the safety/EMC requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request.
Compliance link	https://sp.ts.fujitsu.com/sites/certificates

Warranty

Warranty period	3 years
Warranty type	Onsite warranty
Warranty Terms & Conditions	www.fujitsu.com/warranty

Product Support - the perfect extension

Support Pack Options	Available in major metropolitan areas: 9x5, Next Business Day Onsite Response Time 9x5, 4h Onsite Response Time (depending on country) 24x7, 4h Onsite Response Time (depending on country)
Recommended Service	24x7, Onsite Response Time: 4h
Service Lifecycle	at least 5 years after shipment, for details see https://support.ts.fujitsu.com/
Service Weblink	www.fujitsu.com/services/product-services

Fujitsu products, solutions & services

In addition to Fujitsu ETERNUS AF650 S3, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Built on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offerings. This allows customers to select from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu ETERNUS AF650 S3, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/global/products/computing/storage/all-flash-arrays/eternus-af650-s3/

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>

Copyright 2022 Fujitsu Limited

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering. The product was developed for normal business use.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Limited

Website: www.fujitsu.com/eternus

2023-01-02 WW-EN