

# Product datasheet

Specifications



## APC Easy UPS On-Line SRV 3000VA 230V

SRV3KI

### Overview

<b>Presentation</b>	High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.
<b>Lead time</b>	Usually in Stock

### Main

<b>Main Input Voltage</b>	230 V
<b>Other Input Voltage</b>	220 V 240 V
<b>Main Output Voltage</b>	230 V
<b>Other Output Voltage</b>	220 V 240 V
<b>Rated power in W</b>	2400 W
<b>Rated power in VA</b>	3000 VA
<b>Input Connection Type</b>	IEC 60320 C20
<b>Output connection type</b>	6 IEC 60320 C13 1 IEC 60320 C19
<b>Cable length</b>	1.5 m
<b>Number of cables</b>	1
<b>Provided equipment</b>	1 IEC 60320 C19 to Schuko power cable 1 IEC 60320 C13 to C14 power cable 1 USB cable 1 RS-232 configuration cable user manual

### General

<b>Number of power module filled slots</b>	0
<b>Number of power module free slots</b>	0
<b>Redundant</b>	No

### Physical

<b>Colour</b>	Black (RAL 7010)
<b>Height</b>	33.6 cm
<b>Width</b>	19 cm

Depth	42.5 cm
Net weight	26.8 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Not rack-mountable
USB compatible	Yes
Mounting position	Vertical

## Input

Input voltage limits	110...285 V half load 160...280 V full load
Network frequency	40...70 Hz auto sensing

## Output

Maximum configurable power in VA	3000 VA
Maximum configurable power in W	2400 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Harmonic distortion	3 %
UPS type	Double conversion online
Wave type	Sine wave
Efficiency	88 % (full load)
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1


## Conformance

Product certifications	CE UKCA EAC TISI
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-20...50 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...15000 m
Acoustic level	50 dBA
Heat dissipation	910 Btu/h
IP degree of protection	IP20

## Batteries & Runtime

Battery type	Lead-acid battery
Battery voltage	72 V
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	4 h
Battery life	3...5 year(s)
Replacement battery	<a href="#">APCRBCV205</a> 
Battery charger power	60 W rated

## Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Free slots	1
Control panel	Multifunction LCD status and control console

## Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	46.5 cm
Package 1 Width	32.5 cm
Package 1 Length	56.5 cm
Package 1 Weight	29 kg

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Optimized Energy Efficiency	Energy efficient product

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

## Recommended replacement(s)