

Product datasheet

Specifications



APC Smart-UPS 5000VA 230V Rackmount/Tower

SUA5000RMI5U

Overview

Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Lead time	Usually Ships within 4 Weeks

Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	4000 W
Rated power in VA	5000 VA
Output connection type	8 IEC 320 C13 4 IEC Jumpers 2 IEC 320 C19
Number of rack unit	5U
Battery type	VRLA
Provided equipment	CD with software Documentation CD Installation guide Rack mounting hardware Rack mounting support rails Smart UPS signalling RS-232 cable User manual Web/SNMP management card

General

Number of power module filled slots	0
Number of power module free slots	0
Redundant	No

Physical

Colour	Black
Height	22.2 cm
Width	48.3 cm
Depth	66 cm

Net weight	97.73 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Rack-mounted
Two post mountable	0
USB compatible	No

Input

Input voltage limits	151...302 V adjustable 160...286 V
Number of input connectors	1 hard wire 3-wire
Network frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Crest factor	3 : 1
Harmonic distortion	Less than 5 % at full load
Maximum configurable power in VA	5000 VA
Maximum configurable power in W	4000 W
Transfer time	2 ms typical : 4 ms maximum
UPS type	Line interactive
Wave type	Sine wave
Efficiency	96 % (full load)
Output frequency	47...53 Hz for 50 Hz nominal sync to mains


Conformance

Product certifications	C-Tick CE GOST VDE
Marking	GS Mark
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Acoustic level	53 dBA
Heat dissipation	430 Btu/h
Operating altitude	0...10000 ft
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %

Batteries & Runtime

Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	2
Battery life	3...5 year(s)
Replacement battery	RBC55 
Battery power in VAh	1632 VAh runtime
Battery charger power	542 W rated

Communications & Management

Alarm	Audible and visible alarms : configurable delays
Control panel	LED status display with on line : on battery : replace battery and overload indicators
Free slots	0
Preinstalled device	Network management card LED status display with on line : on battery : replace battery and overload indicators

Surge Protection and Filtering

Surge energy rate	480 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	63.5 cm
Package 1 Width	61 cm
Package 1 Length	76.2 cm
Package 1 Weight	106.82 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	4
Package 2 Height	119 cm
Package 2 Width	100 cm
Package 2 Length	120 cm
Package 2 Weight	464 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes

RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
-----------------	---------------------------

Recommended replacement(s)