FUJITSU

Data Sheet Fujitsu Display P2410 WE CAM

Widescreen 61.13 cm (24.1 inch) superior display The heart of smart workplaces and video conferencing

The FUJITSU Display P2410 WE CAM is an IPS-based widescreen display that combines smart workplace concepts with advanced ergonomics. It comes with a multi-functional USB Type-C hub that makes it ideal for modern and shared workspaces.

Multifunctional USB Type-C means:

- 95W power delivery for external devices

- Transmission of video signals, webcam, data, LAN & audio

It contains a Fujitsu patented solution that generates an All-In-One user

experience with Mini PC ESPRIMO G and LIFEBOOK series.

The factory pre-calibrated display provides high color fidelity for single as multimonitor usage.

KVM function reduces USB hardware needs by using one display for a number of devices.

For an easy log-in and professional video conferencing, the P2410 WE CAM comes with a Microsoft Windows HELLO compatible, bright Full HD Webcam with mechanical lever lock. The directional microphone hides disturbing sounds. Fujitsu innovated the display housing by offering the worldwide first right-hand USB hub that ensures an optimal cable course and is ergonomically perfect for most users.

Retina protection by low blue light panel that culls damaging blue light without any loss or changes of color.

The integrated Autobrightness sensor adapts the brightness of the display to an optimum, saves energy and increases constant productivity due to reduced eye strain.

DisplayView[™] software enables you to configure your monitor easily for remote management and administrative tasks.

Prolonged product lifecycle through feasible firmware updates done by the user.

Focusing on environmental friendliness, the packaging is styrofoam free and solely consisting of cardboard, which is more than 90% recycled.











Technical details

| c. | - | ~ | - 1 | а | C., | - | ж. | | - | - |
|----|---|---|-----|---|---------|---|----|-------|---|---|
| 2 | n | μ | CI | а | е | ы | | n | μ | 5 |
| | | | | | | | | | | |

| | MS Hello compatible WebCam |
|------------------------------------|---|
| | In-Plane Switching (IPS) technology |
| | Color accuracy average DeltaE<2 |
| | DICOM Greyscale Standard Display Function compatible gamma preset Eco button for Eco mode and 4-colored status LED |
| | Presence sensor with PC security solution |
| | Auto Brightness Control (ABC) |
| | Auto Pivot |
| | Workplace Lighting Guide |
| | DisplayView [™] Software |
| | 6-in-1 Stand |
| | Cable guide |
| | Always available USB (in operating and standby mode) |
| | 24/7 usage Integrated speakers |
| | Smart Power ON and LED function for AiO-type usage (in combination with a dedicated FUJITSU systems e.g. |
| | ESPRIMO G or selected LIFEBOOK models) |
| | Low blue light mode |
| Ergonomic stand | |
| Stand | 6-in-1 Stand |
| Height adjust range | 150 mm |
| Picture height over desk (min) | 40 mm |
| Rotation to portrait | 90° clockwise and counterclockwise, Auto Pivot sensor |
| Tilt angle | -5° / +35° |
| Swivel angle | 345° |
| Picture performance | |
| Panel and backlit | In-Plane Switching (IPS) technology/LED |
| Screen Surface Treatment | 3H hard coating, Anti-glare |
| Contrast - typical | 1,000:1 |
| Contrast - advanced | 20,000,000:1 |
| Response time gray to gray typical | 5 ms (in Video mode) |
| Viewing angle (h/v) - typical | 178°/178° CR10:1 |
| Color performance | 16.7 million colors (Hi-FRC) |
| High color gamut - typical | 73% NTSC / 99% sRGB color space |
| Brightness - typical | 300 cd/m ² |
| Size and resolution | |
| Aspect ratio | 16:10 |
| Diagonal Size | 61.13 cm (24.1-inch) |
| Resolution (native) | 1,920 x 1,200 pixel |
| Resolution (interpolated) | 1,920 x 1,080 pixel, 1,680 x 1,050 pixel, 1,600 x 1,200 pixel, 1,400 x 900 pixel, 1,280 x 800 pixel, 1,280 x 768 pixel, 1,024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel |
| Picture size | 518.4 x 324 mm |
| Pixel Pitch | 0.27 mm |
| Frequencies | |
| Horizontal | 30 - 82 kHz |
| Vertical | 48 - 76 Hz |
| Connectivity | |
| DisplayPort | 1 x DisplayPort Out (Daisy Chain), 1 x DisplayPort 1.2 |
| HDMI | 1 x HDMI 1.4 |
| Audio signal output | 3.5 mm stereo phone jack for head phone |
| Audio sound output | 2 x 2 W |
| DisplayPort audio | Yes |
| HDMI audio | Yes |

| USB downstream | 4x USB 3.2 Superspeed 5GBit (1x Type C and 1x Type A on side, 2x Type A on bottom) |
|--|---|
| USB upstream | 1 x USB Type C with alternate mode for video data and power delivery up to 95W 1 x USB 3.2 Gen1 Type B Integrated KVM switch function |
| Ethernet (RJ-45) | 1 x Gigabit LAN PXE, Wake on LAN (from S3), MAC Address Pass Through support with selected LIFEBOOK models |
| Integrated microphone array | Stereo microphone |
| Integrated Web Camera | 2.0 megapixel webcam (full HD) |
| Ease-of-use menu | |
| Notes | 6 tactile keys on front side |
| Direct Access Keys | Menu, ECO, Input, Mode, Audio, Brightness |
| Languages | Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Japanese, Chinese simply, Chinese traditional |
| Brightness / Contrast | Brightness, Contrast, Black level, Auto Brightness, ACR, Lighting Guide |
| Mode | D-Mode, sRGB, Low Blue Light, Office, Photo, Video, Custom |
| Color | 5000K, 6500K, 7500K, Native, RGB Adjust |
| OSD | Language, OSD-Timeout, OSD rotation |
| Image adjust | Expansion, Saturation, Sharpness |
| Audio | Mute, Volume, Input for HDMI and DP interface |
| Information | Model name, Serial number, Signal input, Resolution/mode, Display mode , Color Temperature, ACR Status, ABC Status |
| Advanced settings | Presence Sensor, Proximity Adjust, Daisy Chain, Overdrive, DDC/Cl, Factory Recall |
| Power consumption (typical) | |
| Soft switch off | 0.26 W |
| Power save mode | 0.28 W |
| Operating with EPA settings | 16.65 W |
| Total Energy Consumption (ETEC) | 53.98 kWh/year |
| Operating maximum brightness | 28 W |
| Power supply | integrated |
| Power notes | Speakers off, USB not connected ETEC and EPA refer to ENERGY STAR® 8.0 Power save mode according to EEI test conditions |
| Electrical values | |
| | |
| Rated voltage range | 100 V - 240 V |
| Rated voltage range Rated frequency range | 100 V - 240 V 50 Hz - 60 Hz |
| | |
| Rated frequency range | 50 Hz - 60 Hz |
| Rated frequency range Protection class | 50 Hz - 60 Hz |
| Rated frequency range Protection class Compliance | 50 Hz - 60 Hz 1 |
| Rated frequency range Protection class Compliance Model | 50 Hz - 60 Hz 1 P2410W ENERGY STAR [®] 8.0, TÜV Low Blue Light Certified, TÜV Flicker Free Certified, Zero bright and dark pixel faults, Subpixel |
| Rated frequency range Protection class Compliance Model Global | 50 Hz - 60 Hz 1 P2410W ENERGY STAR® 8.0, TÜV Low Blue Light Certified, TÜV Flicker Free Certified, Zero bright and dark pixel faults, Subpixel faults according to ISO9241-307 (Pixel fault class I), TCO Certified, generation 9, EPEAT® Gold (dedicated regions) |
| Rated frequency range Protection class Compliance Model Global Europe | 50 Hz - 60 Hz 1 P2410W ENERGY STAR® 8.0, TÜV Low Blue Light Certified, TÜV Flicker Free Certified, Zero bright and dark pixel faults, Subpixel faults according to ISO9241-307 (Pixel fault class I), TCO Certified, generation 9, EPEAT® Gold (dedicated regions) EN 62368-1, CE certification according to EC Directive 2004/108/EEC, RoHS, WEEE, IT-Eco-Declaration |
| Rated frequency range Protection class Compliance Model Global Europe Australia/New Zealand | 50 Hz - 60 Hz 1 P2410W ENERGY STAR® 8.0, TÜV Low Blue Light Certified, TÜV Flicker Free Certified, Zero bright and dark pixel faults, Subpixel faults according to ISO9241-307 (Pixel fault class I), TCO Certified, generation 9, EPEAT® Gold (dedicated regions) EN 62368-1, CE certification according to EC Directive 2004/108/EEC, RoHS, WEEE, IT-Eco-Declaration (on customer request) |
| Rated frequency range Protection class Compliance Model Global Europe Australia/New Zealand Germany Russia | 50 Hz - 60 Hz 1 P2410W ENERGY STAR® 8.0, TÜV Low Blue Light Certified, TÜV Flicker Free Certified, Zero bright and dark pixel faults, Subpixel faults according to ISO9241-307 (Pixel fault class I), TCO Certified, generation 9, EPEAT® Gold (dedicated regions) EN 62368-1, CE certification according to EC Directive 2004/108/EEC, RoHS, WEEE, IT-Eco-Declaration (on customer request) TÜV GS |
| Rated frequency range Protection class Compliance Model Global Europe Australia/New Zealand Germany Russia Singapore | 50 Hz - 60 Hz 1 P2410W ENERGY STAR® 8.0, TÜV Low Blue Light Certified, TÜV Flicker Free Certified, Zero bright and dark pixel faults, Subpixel faults according to ISO9241-307 (Pixel fault class I), TCO Certified, generation 9, EPEAT® Gold (dedicated regions) EN 62368-1, CE certification according to EC Directive 2004/108/EEC, RoHS, WEEE, IT-Eco-Declaration (on customer request) TÜV GS EAC |
| Rated frequency range Protection class Compliance Model Global Europe Australia/New Zealand Germany Russia Singapore USA/Canada | 50 Hz - 60 Hz 1 P2410W ENERGY STAR® 8.0, TÜV Low Blue Light Certified, TÜV Flicker Free Certified, Zero bright and dark pixel faults, Subpixel faults according to ISO9241-307 (Pixel fault class I), TCO Certified, generation 9, EPEAT® Gold (dedicated regions) EN 62368-1, CE certification according to EC Directive 2004/108/EEC, RoHS, WEEE, IT-Eco-Declaration (on customer request) TÜV GS EAC S-Mark |
| Rated frequency range Protection class Compliance Model Global Europe Australia/New Zealand Germany | 50 Hz - 60 Hz 1 P2410W ENERGY STAR® 8.0, TÜV Low Blue Light Certified, TÜV Flicker Free Certified, Zero bright and dark pixel faults, Subpixel faults according to ISO9241-307 (Pixel fault class I), TCO Certified, generation 9, EPEAT® Gold (dedicated regions) EN 62368-1, CE certification according to EC Directive 2004/108/EEC, RoHS, WEEE, IT-Eco-Declaration (on customer request) TÜV GS EAC S-Mark FCC Class B, cTUVus |
| Rated frequency range Protection class Compliance Model Global Europe Australia/New Zealand Germany Russia Singapore USA/Canada Compliance link | 50 Hz - 60 Hz 1 P2410W ENERGY STAR® 8.0, TÜV Low Blue Light Certified, TÜV Flicker Free Certified, Zero bright and dark pixel faults, Subpixe faults according to ISO9241-307 (Pixel fault class I), TCO Certified, generation 9, EPEAT® Gold (dedicated regions) EN 62368-1, CE certification according to EC Directive 2004/108/EEC, RoHS, WEEE, IT-Eco-Declaration (on customer request) TÜV GS EAC S-Mark FCC Class B, cTUVus |
| Rated frequency range Protection class Compliance Model Global Europe Australia/New Zealand Germany Russia Singapore USA/Canada Compliance link Dimensions / Weight / Environmental | 50 Hz - 60 Hz 1 P2410W ENERGY STAR® 8.0, TÜV Low Blue Light Certified, TÜV Flicker Free Certified, Zero bright and dark pixel faults, Subpixe faults according to ISO9241-307 (Pixel fault class I), TCO Certified, generation 9, EPEAT® Gold (dedicated regions) EN 62368-1, CE certification according to EC Directive 2004/108/EEC, RoHS, WEEE, IT-Eco-Declaration (on customer request) TÜV GS EAC S-Mark FCC Class B, cTUVus https://sp.ts.fujitsu.com/sites/certificates |
| Rated frequency range Protection class Compliance Model Global Europe Australia/New Zealand Germany Russia Singapore USA/Canada Compliance link Dimensions / Weight / Environmental Dimension without stand (W x D x H) | 50 Hz - 60 Hz 1 P2410W ENERGY STAR® 8.0, TÜV Low Blue Light Certified, TÜV Flicker Free Certified, Zero bright and dark pixel faults, Subpixe faults according to ISO9241-307 (Pixel fault class I), TCO Certified, generation 9, EPEAT® Gold (dedicated regions) EN 62368-1, CE certification according to EC Directive 2004/108/EEC, RoHS, WEEE, IT-Eco-Declaration (on customer request) TÜV GS EAC S-Mark FCC Class B, cTUVus https://sp.ts.fujitsu.com/sites/certificates 532.2 x 59.21 x 368.9 mm |
| Rated frequency range Protection class Compliance Model Global Europe Australia/New Zealand Germany Russia Singapore USA/Canada Compliance link Dimensions / Weight / Environmental Dimension without stand (W x D x H) | 50 Hz - 60 Hz 1 P2410W ENERGY STAR® 8.0, TÜV Low Blue Light Certified, TÜV Flicker Free Certified, Zero bright and dark pixel faults, Subpixe faults according to ISO9241-307 (Pixel fault class I), TCO Certified, generation 9, EPEAT® Gold (dedicated regions) EN 62368-1, CE certification according to EC Directive 2004/108/EEC, RoHS, WEEE, IT-Eco-Declaration (on customer request) TÜV GS EAC S-Mark FCC Class B, cTUVus https://sp.ts.fujitsu.com/sites/certificates 532.2 x 59.21 x 368.9 mm 20.95 x 2.33 x 14.52 inch 532.2 x 212.7 x 382.73 mm |
| Rated frequency range Protection class Compliance Model Global Europe Australia/New Zealand Germany Russia Singapore USA/Canada Compliance link Dimensions / Weight / Environmental | 50 Hz - 60 Hz 1 P2410W ENERGY STAR® 8.0, TÜV Low Blue Light Certified, TÜV Flicker Free Certified, Zero bright and dark pixel faults, Subpixe faults according to ISO9241-307 (Pixel fault class I), TCO Certified, generation 9, EPEAT® Gold (dedicated regions) EN 62368-1, CE certification according to EC Directive 2004/108/EEC, RoHS, WEEE, IT-Eco-Declaration (on customer request) TÜV GS EAC S-Mark FCC Class B, cTUVus https://sp.ts.fujitsu.com/sites/certificates 532.2 x 59.21 x 368.9 mm 20.95 x 2.33 x 14.52 inch |

| Weight (Monitor only) | 4.56 kg |
|-------------------------------------|---|
| | 10.05 lbs |
| Operating ambient temperature | 5 - 35 °C (41 - 95 °F) |
| Operating relative humidity | 10 - 85 % (non condensing) |
| Miscellaneous | |
| Miscellaneous | VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared |
| Color | Marble grey |
| Additional Software | |
| Additional software (optional) | WINDOWS WHQL driver Realtek USB Ethernet Controller driver DisplayView Suite DisplayUpdate Power Delivery Update |
| Additional software (notes) | Use of accompanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration. |
| Package content | |
| Display delivered accessories | DisplayPort data cable 1.8 m Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m USB cable 1m (USB-C to USB-C) USB-cable 1.8 m (USB-A to USB-B) Quickstart flyer Safety notes |
| Display delivered accessories notes | Power cable with IEC-60320-C13, 3-pin connector on display side Data cables and USB cable detachable on display User manual and DisplayView Software is available via download DisplayView Software is necessary for AutoPivot function and Presence Sensor PC security solution |
| Packaging information | |
| Packaging dimension (mm) | 162 x 734 x 450 mm |
| Packaging dimension (inch) | 6.38 x 28.9 x 17.72 inch |
| Weight (packed) | 9.36 kg |
| Weight (packed) (lbs) | 20.64 lbs |
| Order information | |
| Order Code | S26361-K1698-V145 |
| EAN Code | 4065221160243 |
| Country specific order code | BDL:K1698V145-UK - with UK power cable, mandatory for Arabian countries BDL:K1698V145-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed |
| Accessories information | Further helpful options: Stands and Mounting kits: http://www.fujitsu.com/fts/products/computing/peripheral/accessories/desktop/ums/index.html Available Adapters: http://globalsp.ts.fujitsu.com/dmsp/Publications/public/pos-connectivity.pdf |
| Warranty | |
| Warranty period | 3 years (depending on country) |
| Warranty Terms & Conditions | http://www.fujitsu.com/warranty |
| Digital bug fixes | Subject to availability and following their generic release for the product, bug fixes and function-preserving patches for product-related software (firmware) can be downloaded from the technical support at: https://support.ts.fujitsu. com/ free of charge by entering the respective product serial number. For application software supplied together with the product, please directly refer to the support websites of the respective software manufacturer. |
| Spare Parts availability | at least 7 years after shipment, for details see https://support.ts.fujitsu.com/ |
| Service Weblink | http://www.fujitsu.com/emeia/products/product-support-services/ |

More information

Fujitsu products, solutions & services

In addition to Fujitsu Display P2410 WE CAM, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products www.fujitsu.com/global/products/ computing/

Software www.fujitsu.com/software/

More information

Learn more about Fujitsu Display P2410 WE CAM, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/emeia/products/ computing/peripheral/displays

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at http://www. fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/ emeia/resources/navigation/terms-of-use. html

Copyright 2022 Fujitsu Technology Solutions GmbH

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

The overall product has been designed and manufactured for general office use, regular personal use and ordinary industrial use.

CONTACT

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com 2023-02-02 EM-EN All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html Copyright 2022 Fujitsu Technology Solutions GmbH